

LOADCENTRES IP65

HENSEL ENYBOARD

Features and Ratings:

- IP65 and IK08 protection rating.
- Pre-moulded metric knock outs.
- KVPC version is polycarbonate with opaque door ideal for outdoor use exposed to the weather.
- Supplied with Fixconnect E&N bars.



KV...



KVPC...



KVFC...



KVNP...

IP65 LOADCENTRES

No. of Poles	No. of Rows	Part No.
3	1 Row	KV7103
4	1 Row	KV7104
6	1 Row	KV7106
9	1 Row	KV7109
12	1 Row	KV9112M
18	1 Row	KV9118M
24	2 Rows of 12P	KV9224M
36	2 Rows of 18P	KV9236M
36	3 Rows of 12P	KV9336M
48	4 Rows of 12P	KV9448M
54	3 Rows of 18P	KV9354M

- Suitable for indoor or outdoor protected from the weather.

IP65 OPAQUE DOOR LOADCENTRES

No. of Poles	No. of Rows	Part No.
12	1 Row	KVPC0112
24	2 Rows of 12P	KVPC0224
36	3 Rows of 12P	KVPC0336

KEYLOCKS

No. of Enclosure Poles	Part No.
3 - 9	KVES3
12 - 54	KVES1

SPARE EARTH AND NEUTRAL LINKS - FIXCONNECT

Connections		No. of Enclosure Poles	Part No.
Springs ⁽¹⁾	Screws ⁽²⁾		
4	1	3	KVFC03
4	2	4	KVFC04
4	2	6	KVFC06
8	2	9	KVFC09
12	3	12	KVFC12
16	4	18	KVFC18
24	6	24/336/48	KVFC24
32	8	236/54	KVFC36

(1) Suitable for 1.5mm² - 4mm² rigid or flexible conductors without ferrule.

(2) Suitable for 1.5mm² - 25mm² rigid or flexible conductors without ferrule.

SPARE EARTH AND NEUTRAL LINKS - FIXCONNECT

Connections		No. of Enclosure Poles	Part No.
Springs ⁽¹⁾	Screws ⁽²⁾		
3	1	3	KVNP03
3	2	4	KVNP04
4	2	6	KVNP06
6	2	9	KVNP09
10	2	12	KVNP12
16	4	224	KVNP20
20	5	224/336	KVNP25

(1) Suitable for 1.5mm² - 4mm² rigid or flexible conductors without ferrule.

(2) Suitable for 1.5mm² - 25mm² rigid or flexible conductors without ferrule.